


LPE4 OptiLine



Product Description



Flow volume: 8 - 175 l/min

Max differential pressure: 16 bar

Applications: Circulation and transfer

1. Applications

1.1 Functionality

The LPE OptiLine pump is used for a number of different fluids:

Fuel oil, vegetable oil, hydraulic oil and other hydraulic fluids, polymers, emulsions and any non-aggressive fluid with sufficient lubricating properties.

1.2 Applications

Typical applications are:

- Circulation for cooling and filtration in large machineries, hydraulic systems and transformer oil for insulation in transformers
- As transfer pumps onboard vessels, in power plants, oil factories, refineries, tank farms etc
- Fuel supply duties for engines
- Supply and circulation of fuel oil


1.3 Installation

The pump is designed to be flange-mounted to its electric motor via a connecting frame and a magnetic coupling. By the angle bracket, the pump may be mounted horizontally or vertically. For vertical installation, a stand mounted on the rear cover can be supplied (version NxYP)


As standard, the pump is delivered excluding counter flanges (DIN type) but can be included if requested.

As standard the pump is delivered with the discharge side to the left when seen from the pump rear end (see below).

For more information about installation, see Service, Maintenance and Startup Instructions for LPE OptiLine generation 4.



Mounting standard picture M93-0.



On request the pump can be delivered with opposite flow direction, M39-0.

2. Pump model code

L P E 0 2 5 N 4 N K B P

Pump series _____
LPE

Size _____
Power rotor diameter [mm]
025, 032, 038

Lead _____
K and L = Low lead
N = Normal lead
D = High lead

Generation _____
Design generation 4

Material in pump body _____
N = Nodular cast iron

Shaft seal design _____
Magnetic shaft coupling
(Size of coupling selected)
K, L, M, N

Mounting _____
B = Flange mounting
Y = Including stand for vertical installation

Valve _____
P = Pressure relief valve with spring for max. 16 bar

Special design _____
Code group omitted for standard design (A-number)

3. Technical Data

3.1 Pressure Information

Pressure relief valve

The pump is equipped with an integral pressure relief valve with internal return, limiting the differential pressure across the pump and protecting the pump. Should the discharge line be blocked, the relief valve will open by the pressure.

The valve is adjustable for different opening pressures. The value of the pressure limit can be set at the factory and should be adjusted at installation (see Service, Maintenance and Installation for LPE OptiLine generation 4).

The maximum pressure accumulation varies with pump size, speed and viscosity, but will normally not exceed 4 bar.

The valve has a maximum set pressure of 16 bar.

Inlet pressure

Minimum inlet pressure (suction capability) is dependent on fluid viscosity and rotation speed. It increases with decreasing viscosity and decreasing speed. Information about minimum inlet pressure for each individual duty case can be obtained from IMO AB or pump selection software WinPump.

Maximum inlet pressure is 7 bar.

Discharge pressure

Maximum discharge pressure is 16 bar.

Differential pressure

Maximum differential pressure is 16 bar but reduced at low viscosities according to table below

Viscosity [cSt]	1,4	2	6	10	20
Max. diff. pressure [bar]	6,9	8	12,4	15	16

Refer to your IMO representative or use the pump selection software WinPump to determine the exact operating limits.

3.2 Driver information

Driver type

The power from motor to the OptiLine LPE pump is transmitted without mechanical contact over a magnetic coupling. A coupling hub with a set of permanent magnets is mounted on the pump shaft. This hub is totally enclosed by a stainless steel can. The motor hub with another set of permanent magnets rotates on the outside of this can. Thus the pumped liquid is totally confined within the pump without the use of a conventional shaft seal.

The pump is designed for this type of drive only.

Speed

The maximum speed is 3600 rpm. For higher speeds, contact IMO AB.

Rotation

The pump is designed to operate in one rotational direction only, as standard clockwise when facing the shaft end. Pumps for CCW rotation can be delivered on special request. For shorter periods of time, a few minutes for emptying a discharge line, the pump may be operated in reverse direction, provided the back pressure is limited to 3 bar.

3. Technical Data

3.3 Sound level

Typical pump sound levels refer to free field conditions at a distance of 1 m from the pump. Noise of driver excluded in the quoted figures. The sound levels are measured at a discharge pressure of 5 bar, speed 2940 rpm and viscosity 40 cSt, according to ISO-3741.

Size 025 032 038

Sound level dB [A] 58 58 58

3.4 Moment of Inertia

Moment of inertia [10^{-6} kgm 2]

Coupling / size	025	032	038
K	3692	3715	-
L	5730	5753	5908
M	-	6917	7072
N	-	-	7594

3.5 Magnetic shaft coupling

< Torque values (greater than, at least) [Nm]

Coupling	Size		
	025	032	038
K	7	7	-
L	14	14	14
M	-	22	22
N	-	-	30

3.5 Fluid viscosity

OptiLine pumps:
1,4 – 1500 cSt

For higher viscosity, contact IMO AB.

3.6 Fluid temperature

OptiLine pumps:
-20 – +180 °C

4. Design

4.1 Ball bearing

The pump is fitted with an internal ball bearing which continuously is being greased by the handling media.

4.2 Design material

Model	Material pump	Material rotor	Material idler	Material seal	Material Elastomers
LPE	Nodular cast iron	Steel, surface treated	Cast iron, surface treated	-	Viton

4.3 Steam tracing


During cold start-up conditions, high viscosity could cause the rated torque for the coupling to be exceeded.

The IMO OptiLine pump series have a way to warm up the pump by leading steam into small channels at the front cover. This is recommended if cold upstart can be assumed.

See Pump Unit Dimensions for dimensions of the connections to the steam system.

5. Performance

Typical performance values at 5 bar
Flow calculated at 26 cSt, power at 260 cSt.




rpm	025L		025N	
	l/min	kW	l/min	kW
1470	8,5	0,3	12,1	0,4
1770	11,5	0,4	16,3	0,5
2950	23,1	0,8	32,7	1,0
3550	28,9	1,1	41,0	1,3

rpm	032L		032N	
	l/min	kW	l/min	kW
1470	21,4	0,5	34,5	0,7
1770	27,5	0,6	43,2	1,0
2950	51,8	1,4	77,5	1,9
3550	64,2	1,9	95,0	2,5

rpm	038K		038N		038D	
	l/min	kW	l/min	kW	l/min	kW
1470	44,0	1,3	54,3	1,2	57,6	1,3
1770	57,1	1,6	69,1	1,5	74,8	1,6
2950	101,5	3,4	127,0	3,2	143,9	3,4
3550	124,7	4,3	156,5	4,1	176,8	4,3

6. Sectional view



7. List of components

Pos No	Denomination	Pos No	Denomination
002	Motor	401	Pump body
003	Connecting frame	440	Expander plug
004	Angle bracket	451	Screw
005	Magnetic coupling	453	Screw
005A	Retaining ring	462	Plug
006A	Screw	462A	Sealing washer
007A	Screw	463	Plug
007B	O-ring	463A	Sealing washer
1020	Complete power rotor	5010	Front cover
(112)	Balancing piston	502	Plug
113	Key	506	Gasket
122	Ball bearing	551	Rear cover
124	Retaining ring	556	Gasket
124A	Support ring	584	Vertical stand
202	Idler rotor	588	Screw
351	Balancing bush	588A	Washer
		701A	Washer
		701B	Nut
		702	Screw
		702A	Washer
		703	Screw
		703A	Washer
		703B	Nut
		998	Drive hub
		998B	Screw
		6000	Complete valve element
		(605)	O-ring
		(608)	Valve spindle
		(608A)	Tension pin
		(6120)	Complete regulating nut
		(613)	Pin
		(614)	Valve piston
		(615)	Valve spring
		701	Screw


Drawing remarks:

- (1) Applicable for face mounted execution code xxBx
- (2) Applicable for vertical mounted execution code xxYx

Notes:

- Components with Pos No within parenthesis are parts of subassembly

8. Pump dimensions



8. Pump dimensions

Pump size	IEC No	Frame size	Main dim.												Foot dim.				Flange dim.				Outlet				Inlet				Weight			
			A	A	B	B1	C	D	F	V	E	E1	E2	E3	H	HG	J	K	L ¹	LG	N	O	P	Q	Q1	R	S	T	U	U1	Cog	Cog	kg	kg
025	80	F165	303	366	81	75	140	86	163	140	138	190	17	11.5	7	8	140	160	120	11	115	85	25	M12	20	115	85	25	M12	20	24	166	20	24
	90	F215	338	401						175																					34	154	19	23
032	80	F165	339	401						140																					32	163		
	90	F215	374	436	87	85	162	99	199	175	152	190	17	11.5	7	8	140	160	120	11	140	100	32	M16	25	140	100	32	M16	25	48	170	25	29
038	132	F265	395	457							196																				57	178		
	90	F165	346	426						140																					48	188	26	30
xe- xer- ode	100	F215	381	461	89	110	191	95	206	175	153	190	17	13.5	7	8	140	160	120	11	165	125	50	M16	25	165	125	50	M16	25	67	193	27	31
	112	F265	402	482						196																					71	193	31	35
	132	F265	402	482																											67	194	32	36
																															54	207	34	38
																															xxBx	xxYx	xxBx	xxYx

Drawing remarks:


- (1) Inlet gauge: ISO G1/8
- (2) Relief valve. Turn clockwise to increase opening pressure
- (3) Connection for heating. ISO G1/8

(4) Other side: Outlet gauge, ISO G1/8
(5) Nut, washer and stud M10 included in delivery for mounting to connecting frame

Notes:

- Dimensions in mm
- Counter flanges according to DIN2633/ND16
- 1) Tolerances ISO n7

9. Pump Unit dimensions



9. Pump Unit Dimensions

Drawing remarks:

(1) Inlet gauge. ISO G1/8

(2) Relief valve. Turn clockwise

(3) Space for dismantling

'4) Connection for heating. ISO G1/8

(5) Other side: Outlet gauge. ISO G1/8

6) For vertical stand dimensions see [page 10](#)

Notes:

Dim -

Dim
tors

Foot -

10. Accessories

A bare shaft pump (Fig. 1) can be ordered with the accessories in fig. 2-7.




Fig. 1 Bare shaft pump



Fig. Set of counter flanges




Fig. 3 Connecting frame



Fig. 4 Electric motor



Fig. 5 Angle Bracket



Fig 6. Vertical stand



Fig. 7 Gauge panel

11. Maintenance

Spare parts for these pumps are easily available from stock. For detailed information and know-how about service, see the Service, Maintenance and Startup Instruction for LPE4 Opti-Line pumps or contact IMO AB.



**For latest updates, check:
www.imo.se**